

Clinical Chemistry

Selectra ProS™



Selectra Solutions

THE SMARTEST CHOICE
FOR LABORATORIES
LOOKING TO AUTOMATE



VitalScientific
Diagnostics for Life

Clinical Chemistry

SPECIFICATIONS

THROUGHPUT

- Up to 133 tests/hour
- Up to 333 ISE tests/hour

REAGENT AND SAMPLE HANDLING

One rotor combining both sample and reagent positions. Reagent ID and automated programming of assays, calibrators and controls via barcode.

- Inner rotor ring:
 - 30 refrigerated reagent positions for 10 mL and 25 mL reagent bottles
 - Cooled to 10°C +/-4°C at normal laboratory conditions
 - All reagent positions can be assigned as R1, R2 and R3
- Outer rotor ring:
 - 25 barcode readable positions
 - All positions fit 13x75 mm primary and secondary tubes and pediatric cups
 - All positions can be used for calibrators, controls, normal, pediatric and STAT samples

PIPETTING SYSTEM

- 1000 µL reagent syringe:
 - R 1 volume 110 - 399 µL
 - R 2 volume 10 - 289 µL
 - R 3 volume 10 - 289 µL
 - Programmable in 1 µL steps
- 100 µL sample syringe:
 - Sample volume 1 - 30 µL
 - Programmable in 0.1 µL steps
- Programmable dilution ratios: 1 : 5 up to 1 : 200 in one step increments with 3 possible diluents
- Pre-heated probe with level detection, collision protection and integrated mixer

CUVETTE ROTOR

- Cost effective, semi-disposable cuvette rotor with 48 cuvettes, path length 7 mm
- >10,000 tests per rotor
- Minimum measuring volume 220 µL
- Measuring temperature 37°C, controlled by Peltier elements

LIGHT SOURCE

- Quartz-iodine lamp 12V-20W

WAVELENGTH RANGE

- 340 - 800 nm
- Optical unit with 8 position filter wheel
- Automatic wavelength selection
- 340, 405, 505, 546, 578, 620, 660, 700 nm standard installed
- Other wavelengths available on request

PHOTOMETRIC RANGE

- -0.1 to 3.0 Absorbance
- Resolution 0.001 Abs

ANALYTICAL MODES (SINGLE, DUAL AND TRIPLE REAGENT SYSTEM)

- Kinetic measurement with linearity check
- Mono and bichromatic end point measurement with or without bichromatic reagent blank and/or sample blank correction
- Two point measurement; with or without slope blank
- Graphic plot of all measuring points
- Predilution, post-dilution and automatic reflex dilution as needed
- Non-linear calibration curves
- Prozone check for immunology tests
- Cut-off declaration
- Calculated tests

QUALITY CONTROL

- Up to 15 different controls can be defined, 3 per test
- Westgard rules
- Levey-Jennings plots
- Quality control statistics

WATER CONSUMPTION

- ~950 mL per hour max, continuous operation

STANDARDS AND REGULATIONS

- CE-IVDR
- USA FDA 510(k)
- CB
- UL

DIMENSIONS & WEIGHT

- 83cm (33in) x 59 cm (23in) x 61 cm (24in) excl. monitor and panel PC (WxHxD)
- 75 kg (165 lbs)

INTERFACE

- State of the art Host-Query interface available
- Host: RS232 or Ethernet (TCP/IP) through LIS-2A protocol
- Hand held CCD barcode reader used for reagent identification and automated programming of assays, controls and calibrators

INSTALLATION CONDITIONS

- Temperature: 15 - 32 °C (59 - 90°F)
- Humidity: 15 - 85% RH
- Altitude: up to 2000 m
- Plumbing: no dedicated system water or drain required
- Electrical: Voltage: 100 - 240 Vac; Frequency: 50/60 Hz; Power (max): 400 VA

INTEGRATED PC*

- Touch screen navigation
- Operating System: MS Windows 10 IoT

OPTIONS

ISE MODULE*

- Patented Solid State Dry Electrode Technology
- Indirect measurement
- Dilution 1:14
- Measures Sodium, Potassium, Chloride and Bicarbonate

POSITIVE SAMPLE IDENTIFICATION

- Positive Sample Identification (PSID) via integrated barcode reader
- Reads all popular formats including Codes 39, 128, 11, 93, CODABAR and Interleaved 2/5

PRINTER

- Printer supported by MS Windows™

PROACTIVE MAINTENANCE KIT

- Complete parts kit for annual preventive maintenance

* Please verify the right instrument catalog number for this option from your local representative.



VitalScientific
T +31 (0)31 3430500
info@vitalscientific.com

©2024, VitalScientific, The Netherlands



www.vitalscientific.com